



HANDFORGED
TRADITIONAL
IRONMONGERY

A GUIDE TO:

Buying and fitting surface mounted door knockers

We manufacture eight differing styles of Door Knockers, which come in a multitude of finishes but there are two different types of fixings used to attach the products to your door, 'Bolt-through' and 'Surfaced Fixed'. The fitting instructions contained in this guide are for the 'Surfaced Fixed' type of door knocker (please see our guides menu on the website for all the different instructions available).

Listed below are the various parts that come in our Ring Door Knocker Set with all surface fixed knockers coming with the same parts. See over for full fitting instructions but bear in mind that a certain amount of care would be needed to fit one although carpentry skills are not necessary, just a pencil, a drill, drill bits and a hammer.

RING DOOR KNOCKER



Ring Door Knocker
33658 - Pewter Patina Finish




Slotted Screws x4



Strike Pin



Disclaimer: These fitting instructions are designed as a guide only and no responsibility can be taken by From The Anvil or it's stockists regarding damage to your property or product. It is advised that you seek professional advice before attempting this process.



HANDFORGED
TRADITIONAL
IRONMONGERY

A GUIDE TO:

Fitting a surface fixed Door Knocker (Ring Knocker featured)

STEP 1



Fitting a surface fixed Knocker is a very simple job but some care must be taken when marking out and drilling to get a good alignment on your door. Start by deciding where on your door the knocker is to be fitted avoiding any mouldings, windows or ironmongery and remember not too far up on the door to suit all heights.

STEP 2



Use a pen or pencil to mark out the four fixing holes of the backplate making sure to hold the product firmly in place so that it doesn't move.

STEP 3



Remove the product and using a 2mm drill bit make a hole whilst taking care not to scratch your door surface.

Repeat this process for the other three marks.

STEP 4



Put the first screw in to the backplate and partly screw into the door. Take care and time with the From The Anvil screws as they are all hand-made. Repeat the process for all screws partially fixing them to check that your product position hasn't slipped. Carefully tighten all screws so the product is firmly attached to the door.

STEP 5



The next few steps are to affix the strike plate.

Mark underneath the knocker, where it is going to strike against the door, lift the knocker out of the way to make it easier for you to put a mark where a pilot hole needs to be drilled.


STEP 6



Drill a pilot hole using a 3mm drill bit where you have placed your mark. This helps when fixing the strike plate.

If you do not drill a pilot hole there may be a tendency for the wood/composite door to split on step seven.

STEP 7



Place the supplied strike plate into the hole you have just drilled and gently hammer into place taking care that you do not split the door material.

STEP 8



Once the strike plate is firmly in place the job is complete and you are now able to use your From The Anvil door knocker.

Test the product to make sure all items are firmly affixed and then await your first visitor!